

IPC CONTROL SYSTEM

Industrial personal computer (IPC) control system can realize the function of real-time readings display, history record, concentration curve, remote control (via PLC) and other functions.

The IPC system is a customized solution, which can support up to 500 detection data, and customized functions according to different requirement. The system is mainly composed of industrial computer and monitoring software.

Functions

- Historical and real-time concentration curve query.
- Displays the concentration information in map, much visual.
- Red, yellow, green three-color light alarm for each detection point.
- Alarm record query, including historical alarm record, alarm time, recovery time.
- Various information such as date, time, bit number, description, unit, alarm value, alarm type etc.
- Customized user interfaces and functions based on different requirement.





Gas detection system can be widely applied in places such as petrochemical engineering, chemical engineering, steel, metallurgy, pharmaceuticals, electricity, food, and logistics where the monitoring of flammable and toxic gas is needed.

The system is made of gas detector, controller and sound-light alarm, and the gas concentration data will be uploaded to the control panel. The controller collectively displays the gas concentration data of different monitoring points, and the sound-light alarm will be set off in case that any concentration exceeds over the default value. Linkage feature can be realized and the data can be also uploaded to host systems such as DCS/IPC.

FUNCTION




DIAGRAM of GAS DETECTION SYSTEM

1. gas detector

The gas detector is fixed in areas such as the workshop, warehouse, and storage tank for real-time monitoring of the concentration of flammable and toxic gases.

2. zone control

The controller collectively displays the gas concentration, and the sound-light alarm will be set off in case that any concentration exceeds over the default value.

3. The interlock control

It comes with relay output and fault output for the performing of automatic fan, spray, valve, and alarm.

4. The host computer

Standard 4-20mA and RS485 signal output, compatible with host computers such as DCS/PLC/IPC.



SELECTION GUIDE

QUICK SELECTION TABLE 1 -- FIXED GAS DETECTOR

		A	AG310 serie	es			AG21	0 series		A	G200 ser	ies
Description	GTQ- AF110	GTQ- AF111	AF110-R	AG310	AG311	AG210	AG211	GTQ- Anr-A	GTQ- Anr-D	AG200	Anr-N	Anr-S
Gas detected												
combustible gas-catalytic	•	•	-	-	-	-	-	•	•	-	•	•
combustible gas-infrared	-		•		-	-	-	-	-	-	-	:
toxic gas-electrochemical	-	-	-	•	•	•	•	2	120	•	-	746
toxic gas-PID	-	-	-	•	•	•	•	-	-	•	=	-
toxic gas-infrared	-	-	-	•	•	•	•	-	1-1	•	-	-
toxic gas-semiconductor	-	-	-	•	•	-	-	-	-	-	=	-
Display												
OLED	•	•	•	•	•	_	- 2	-	123	-	-	-
LCD	-	-	-	8.7.3	-	•	•	•	•	-	-	7-9
Signal output												
4-20mA	•	-	•	•	-	•	5.73	•	-	•	•	-
RS485	-	•	-	29-1	•	3-0	•	-	•	•	-	•
Wiring												
three-wire	•	-	•	•	-	•	-	•	-	•	•	-
four-wire	-	•	-	-	•	_	•	-	•	•	-	•

Note:

- 1. means available, means unavailable;
- 2. both oxygen and toxic gas are detected in electrochemical principle, so the toxic gas includes oxygen in the above table.

QUICK SELECTION TABLE 2 -- CONTROL PANEL

Description	AGS1600F	AGS1000	AGS1000B	AGS1000D	JUDD	JUDD-S
Gas detected						
combustible gas	•	•	•	•	•	•
toxic gas	724	•	•	•	•	•
Display						
LCD	•	•	•	•		-
OLED	-	-	-	170	•	•
Signal input						
4-20mA	•	•	•	•	•	•
RS485	-	•	•	•	- 2	<u> </u>
Wiring						
three-wire	•	•	•	•	•	•
four-wire	-	•	•	•	-	-
Channels	4	1-64	1-64	1-64	1-8	32-128
Installation						
wall-mounted type	•	•	•	•	•	-
cabinet type	-	14	=	-	- 4	•
UPS	-	-	•	-	-	-
Explosion-proof	-		<u>-</u>	•	-	-

Note: The channels of AGS1000, AGS1000B, AGS1000D, JUDD, JUDD-S can be customized.

í		
į		
(
ĺ		
6		
ζ	,	
7		
`		
•	4	
ļ		
ž	Y	
E		
į		
١		
Ę		
į		
ζ	,	
1		
į		
c		

(
• • •
•
•
•
•
• 1 1 1 1 1 1
1%LEL 1%LEL 0.1%VOL 1µmol/mol 1µmol/mol 0.1µmol/mol -
1%LEL 1%LEL 1%LEL 1mol/m emical lµmol/m emical lµmol/m
Catalytic Infrared Electrochemical /mol Electrochemical
Catalytic Infrared Electrochemical

Note: 1. Any gas that not mentioned above, just contact AIYI Technologies for further information; 2, 1µmol/mol=1ppm







TEL:0086-25-87787361 WEB:www.AIYITEC.com

FAX: 0086-25-87787362 EMAIL: sales@autequ.com

Authorized Distributor:

Disclaimer: All pictures, configurations and parameters in this document are for reference only. There may be differences with the actual products. Any difference is subject to the latest real products.